




## PIPE PILE

Deep Foundation Pile Systems > Pipe Pile > Straight Seam



OD Inch	Pipe Sizes Inch	Schedule/Wall Thickness								Note: Weight per foot indicates a mills capability.						
		Inch								3/16 0.188	1/4 0.250	5/16 0.313	3/8 0.375	.400 0.400	1/2 0.500	5/8 0.625
		10	20	30	40	STD	60	80	XS							
8.625	8.00		<u>.250</u> 22.38	<u>.277</u> 24.72	<u>.322</u> 28.58	<u>.322</u> 28.58	<u>.406</u> 35.67	43.42 8	43.42 8	16.912	22.382	27.812	33.072	35.170	43.428	
9.625	9.00									18.916	25.055	31.158	37.081	39.446	48.773	60.131
10.750	10.00		<u>.250</u> 28.06	<u>.307</u> 34.27	<u>.365</u> 40.52	<u>.365</u> 40.52	<u>.500</u> 54.79	<u>.594</u> 64.49	<u>.500</u> 54.786	21.171	28.061	34.922	41.591	44.257	54.786	67.648
12.750	12.00		<u>.250</u> 33.41	<u>.330</u> 43.81	<u>.406</u> 53.575	<u>.375</u> 49.61	<u>.562</u> 73.22		<u>.500</u> 65.476		33.406	41.614	49.608	52.809	65.476	81.010
13.375											35.077	43.705	52.114	55.481	68.817	85.186
14.000	14.00	<u>.250</u> 36.75	<u>.312</u> 45.65	<u>.375</u> 54.62	<u>.438</u> 63.36	<u>.375</u> 54.62	<u>.594</u> 85.13		<u>.500</u> 72.158		36.747	45.796	54.619	58.154	72.158	89.362
16.000	16.00	<u>.250</u> 42.09	<u>.312</u> 52.32	<u>.375</u> 62.64	<u>.500</u> 82.848	<u>.375</u> 62.64			<u>.500</u> 82.848		42.092	52.488	62.637	66.706	82.848	102.724
18.000	18.00	<u>.250</u> 47.44	<u>.312</u> 58.99	<u>.438</u> 82.23	104.7 6	<u>.375</u> 70.65			<u>.500</u> 93.54		47.437		70.654	75.258	93.538	116.087
20.000	20.00	<u>.250</u> 52.78	<u>.375</u> 78.67	104.2 3	123.2 3	<u>.375</u> 78.67			104.2 3		52.782		78.672	83.810	104.228	129.449

Note: Rolling of some sizes and gauges are subject to accumulation - please check rolling schedule or contact sales.  
 ASTM A500 Grade B & C, A252 - CSA G40.21 50W or metric 350W available  
 ASTM A252 for .625" Gauge only available in 16", 18", and 20"